

EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-01

Subject: Emergency IT Equipment's

Sr.	Description		Unit	Qty	Rate	Amount
	Tender Specific	cations for IT Equipment (Required on Turnkey Basis)				
1	Branded All in One	•	NO	10		
		Intel® Core™ i5-12450H, 8C (4P + 4E) / 12T, P-				
	Processor	core 2.0 / 4.4GHz, E-core 1.5 / 3.3GHz, 12MB				
	Graphics	Integrated Intel UHD Graphics	1			
	Chipset	Intel SoC Platform	1			
	- Cpoet	8GB SO-DIMM DDR4-3200 (Max Memory	1			
	Memory	support 16GB)				
	Slots	Two DDR4 SO-DIMM slots, dual-channel capable				
	Storage	256GB SSD M.2 2280 PCIe® 4.0x4 NVMe® Opal 2.0				
	Optical	DVD±RW	1			
	Audio Chip	High Definition (HD) Audio, Realtek® ALC256 codec				
	Speakers	3Wx2, Camera HD 720p, Microphone 2x, Array				
	Power Supply	90W 89% Adapter				
	Display	23.8" FHD (1920x1080) IPS 250nits Anti-glare, 72% NTSC				
	Keyboard	USB Calliope Keyboard, Black, English (UK)	1			
	Mouse	USB Calliope Mouse, Black				
	Expansion Slots	Two M.2 slots (one for WLAN, one for SSD)	1			
	Ethernet	Integrated 100/1000M	1			
		WLAN + Bluetooth® Intel Wi-Fi® 6 AX201,	1			
	Wireless	11ax 2x2 + BT5.1				
		• 2x USB 2.0 • 2x USB 3.2 Gen 2 • 1x HDMI®-				
	Door Dorto	out • 1x Ethernet (RJ-45) • 1x power				
	Rear Ports	connector				
	Warranty	1 Year Local Warranty				
		Manufacturer Authorization Letter (Genuine and verifiable from Manufacturer) is mandatory to submit along with the bid.				
	Authorization					
2	UPS for PC		_			
	Capacity (P.F .6)	1500VA/900W				
		INPUT				
	Walter	100V/110/120VAC+25% or 220V/230V/230V/240VAC/+10% (-35%		40		
	Voltage	optional)				
	Frequency	50/60Hz+1%(Auto Sensing) OUTPUT				
	Voltage	100V/110/120AC+10% or 220V/230V/240VAC +10%				
		50/60Hz+1% (Auto Sensing)				
	Frequency	sine wave				
	Waveform Crost Factor					
	Crest Factor	3:01				
	Transfer Time	Typical 4ms-6ms,				
	20111	BATTERY				
	DC Voltage	24v				
	Configuration	2x12V/7.0AH	NO		<u> </u>	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



	Typical Recharge Time	4- 5 hours				
	Back-up Time	10-15 minutes		1		
		PROTECTION				
	Full Protection	Short circuit, Battery over-charge and over discharge protection				
		Enviroment	1			
	Humidity	20~90RH@0~40'C (non-condensing)	-			
	Noise Level	<45db (1m)		No 1		
		MISC FEATURES				
		LED Display, Power Factor 0.6, Micro	-			
		Processor based Digital Control, Boost and				
		buck AVR for Voltage stabilization, Frequency				
		adaptive, Humanized Alarm System,				
		Automatically Diagnose when starts, Cold				
		Start, Auto restart while AC is recovering, simulated Sine Wave output, Intelligent				
		Battery Management, Short Circuit and Over				
		discharge protection, Automatically charging				
		battery at UPS off				
	Warranty	1 Year Local Warranty				
		Distributor Authorization Letter from Channel				
	Authorization	Distributor (Genuine and verifiable) is				
		mandatory to submit along with the bid.				
3	Multimedia Projecto	r with Screen	No	1		
3	Projection System	DLP Single 0.48" WUXGA				
	DMD type	DC3 DMD Chip				
	Native Resolution	1900-2000 x 1200-1400 pixels				
	Brightness	5,000-6,000 ANSI Lumens				
	Contrast Ratio	100,000 : 1	1			
	Display Color	1 Billion Colors	1			
	Aspect Ratio	Native 16 : 10 (5 aspect ratio selectable)	1			
	Projection Size	30" ~ 300"				
	Throw Ratio	1.36 ~ 2.18	1			
	Zoom Ratio	1.6x				
	Lens Control	Manual Zoom and Focus				
	Lens Shift	Manual lens shfit, V: ±60 %; H: ±23 %	1			
	Light Source Type	Laser				
	Light Source Life	20,000 Hours	1			
	Keystone		-			
	Adjustment	2D keystone, V: ±30 degree; H: ±30 degree VGA (640 x 480) to WUXGA_RB (1920 x 1200)	-			
	Resolution Support	*RB-Reduced Blanking"	-			
	Horizontal Frequency	15 ~ 102KHz				
	Vertical Scan Rate	24 ~ 120 Hz	1			
	HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p				
	Video Compatibility	NTSC, PAL, SECAM				
	Built-in Speaker	10W	-			
	Security	Security Bar	-			
	Features	Digital Shrink and Shift, Image Memory, Projector/ Remote Control ID Setting, Auto High Altitude Mode, HDBaseT, LAN Control, 360_Projection, Dust-Proof Filter				
	Power Supply	100 ~ 240V AC	-			
	Power					
	Consumption	(Max / Normal / Eco) 530 W / 475 W / 365 W				



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

	Voice Over IP Wire (01 years warrant	eless Headsets for Control Room Management y)	No.	200	
i		k SSD 1 TB Storage Capacity (02 years warranty)	No.	40	
,	PC UPS Extra Lithi	um Batteries (12V,7AH)	No.	100	
ļ	Wireless Keyboar	d & Mouse (one year warranty)	No.	40	
	Authorization	Distributor Authorization Letter from Channel Distributor (Genuine and verifiable) is mandatory to submit along with the bid.			
	Warranty	2 Years Local Warranty			
	Installation	Installation of Complete set Multimedia Projector and Screen with Ceiling Mount Kit, Power cable, HDMI Cable Fiber, with Ducting and labour			
	Screen	Projection Screen 5X7 feet Motorized			
	Accessories Standard	Power Cord, Remote control (RCA011), Lens cover, AAA Battery x 2, Installation Guide / Regulatory Statement (Combined), Warranty card (by sku) Anti-dust Filter			
	Operating Temp	0 ~ 40ºC			
	Audible Noise	37 / 35 dBA			
	Standby Consumption	Normal < 0.5W, Network <2W			

Note: IT equipment's must be branded/ genuine and having local warranty



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot- 02

Subject: Training & Preparedness Materials

	Description	on	Unit	Qty	Rate	Amoui
Suppl	y of SMD Screen I	Large	NO	04		
1	Back Type	Backlight Integration				
2	Diasgonal Aspect Ratio	16:09				
3	Display Proportion	1920x1080				
4	Display Colors	16.7M				
5	Viewing Angle	H 178 x V 178				
6	Luminance (nits)	450cd/m ²				
7	Contrast	5000:1				
8	Sound Mode	Standard				
9	Response time	5Ms				
10	Life	More than 60,000				
11	Power supply	AC100~240V 50/60 HZ				
12	Max. Consumption	<180W				
13	Standby Consumption	<3W				
14	Exterior Color	Black (default) gold silver				
15	Color System Support	PAL/NTSC/SECAM				
16	OSD Language	English				
17	Haze Value	10%				
18	Video Format Support	MPEG1/MPEG2/MP EG4/DIVX/ASP/W MV/AVI				
19	Image Format Support	JPEG/BMP/TIFF/P NG/GIF				
20	Audio Format Support	Wave/MP3/WMA/ AAC				
21	Splicing Display	Support				
22	Working Temperature	0∘ C-50∘C				
23	Working Humidity	10%-85%				
24	Storage Temperature	0° C-50°C				
25	Storage Humidity	5%-95%				
26	Cooling	Low noise fans				
27	Application condition	Indoor/Semi Outdoor				
28	Material	Cold-roll steel SPCC				
29	Frame Color	Black, Gold, Silver				
30	Mount/Installa tion Type	Standing, iPhone seamless design				
31	Quality Standard	ISO9001,CCC,RoHS, FCC				
31						



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



2.	Supply	of SMD Screen	Medium		No	04		
	1	Back Type	Backlight Integration					
	2	Diasgonal Aspect Ratio	16:09					
	3	Display Proportion	1920x1080	-				
	4	Display Colors	16.7M					
	5	Viewing Angle	H 178 x V 178					
	6	Luminance (nits)	450cd/m ²	-				
	7	Contrast	5000:1					
	8	Sound Mode	Standard					
	9	Response time	5Ms					
	10	Life	More than 60,000					
	11	Power supply	AC100~240V 50/60 HZ					
	12	Max. Consumption	<180W					
	13	Standby Consumption	<3W					
	14	Exterior Color	Black (default) gold silver					
	15	Color System Support	PAL/NTSC/SECAM					
	16	OSD Language	English					
	17	Haze Value	10%					
	18	Video Format Support	MPEG1/MPEG2/MP EG4/DIVX/ASP/W MV/AVI					
	19	Image Format Support	JPEG/BMP/TIFF/P NG/GIF					
	20	Audio Format Support	Wave/MP3/WMA/ AAC					
	21	Splicing Display	Support					
	22	Working Temperature	0° C-50°C					
	23	Working Humidity	10%-85%					
	24	Storage Temperature	0° C-50°C					
	25	Storage Humidity	5%-95%					
	26	Cooling	Low noise fans					
	27	Application condition	Indoor/Semi Outdoor					
	28	Material	Cold-roll steel SPCC					
	29	Frame Color	Black, Gold, Silver					
	30	Mount/Installa	Standing, iPhone					
		tion Type	seamless design					
	31	Quality Standard	ISO9001,CCC,RoHS, FCC	1				
			Total Amount	<u> </u>		1	1	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-03

Subject: Height Rescue Equipment's.

ir.	DESCRIPTION	UNIT	QTY	RATE	AMOUN'
RESCU	UE ROPE:	No.	110		
Specif	fications:				
•	Static strength: 30-35kN				
•	Static strength fig 8 knot: 15-20kN				
•	Static strength fig 10 knot: 20-25kN				
•	Elongation: 5-10%				
•	Outer plait (sheath): 15-20, Outer braids: 30-35, Inner core: 10-15				
•	Material: Polyamide core/ Polyamide sheath				
•	Weight: 75-100g per metre				
•	Standard length up to 150-200ft				
SINGL	LE PULLY:		110		
Specif	fications:				
•	Strength: 30-40kN				
•	Max 10-15mm rope				
•	Material: High grade alloy				
•	Side plate size: Height 90mm				
•	Width: 52mm				
•	Weight: 158g				
DOUE	BLE PULLEY		110		
Specif	fication:				
	Strength: 30-40kN				
•	Max 10-15mm rope				
•	Material: High grade alloy				
•	Side plate size: Height 105-115mm				
•	Width: 50-60mm				
•	Weight: 250-300g				
D-RING			110		
Specifi	cations:				
•	Single Slot D-Ring Cranked 35-40 Degree				
•	Drop Forged Steel				
•	100% proof loaded to 16-20kN				
•	Min tensile strength 20-25kN				
•	Weight: 100-150gm				
DESCE	NDER		110		
Specifi	cations				
Materi	ial: Aluminium body and stainless steel components				
Loadin	·				
Weigh [.]	t: 2-3kg				
ZIPLIN	E PULLY		110		
	cations				
•	Clip on cover system for easy installation				
•	Double ball bearings ensure constant efficiency				
	regardless of the users weight				
•	Maximum cable diameter: 10-15mm				
•	Weight: 400-500 g				



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



 Breaking strength: 20-25 kN Maximum speed: 50-100kmpr 			
ASCENDER Specifications: • Rope size: 10 to13mm • Material: Anodised aluminium • Weight: 400-500g	11	0	
 WADER FOR DERT RESCUER Specification Trilaminate Fabric - tough, waterproof and resistant to tearing. Double Glue and Tape seam technology. Stitch-Free bonded seams on the Outer Seams. Belt straps with elasticated section for improved comfort Drawcord Waist with toggle for adjustment. Internal front Chest Pocket with zipper D-Ring Loops under each front buckle - easy hang points. Genuine Buckles - strong, durable and replaceable. Double Layered Knees with soft insert for additional durability and protection 	50		
Total Amount			



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA





Specifications Lot-04

Subject: SCBA Complete Kit

<u> 5u</u>	Subject: SCBA Complete Kit								
Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT				
1.	Supply/ commissioning/testing of the SCBA Complete Kit of the following specifications: -	NO	15						
	Air Supply Cylinders: - The latest in composite design to reduce weight Cylinder pack configurations for enhanced balance and reduced profile Cylinder valve of ratchet type to minimize risk of accidental closure Optional direct reading pressure gauge Cylinder capacity is 9 liters. Operation time is 60 minutes with 300 bar. Harness and Back plate: - Designed with the ergonomics of different work situations in mind the QS-Harness features: Easily adjustable, wide, padded shoulder straps and waist belt Individually pivoting shoulder and waist straps that give maximum ease of movement and keep the weight where it belongs, on the hips Anatomically shaped "open type" carrying								
	 frame for added comfort and increased ventilation The possibility to take a wide range of cylinder sizes, carried as single, twin or cylinder packs 								
	 Face Mask: - The S-face mask is an enhancement of the well- known Spiromatic mask, recognized as being the most comfortable on the market and features: Easy work of breathing at all times due to unique balanced breathing valve Activated from inner mask triggering instant response to air demand Built in ambient air hatch for standby use or first breath activated Automatic positive pressure with high air flow, exceeding 500 litres per minute Wide angle vision and low profile Proven, robust design, simple to service and maintain 								
	Possibility for a large variety of accessories to								



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



be easily fitted		
 Regulator Unit: - The flexibility of the Interspiro QS-System where, for instance, a built in rescue hose or Revit ox resuscitation unit may be fitted, places high requirements on the regulator: High capacity flow rates, over 1350 liters per minute • Gives full capacity down to very low cylinder pressures 		
 Light, small, balanced regulator giving stable secondary pressure Rugged design with few parts and minimal 		
 wear Proven pneumatics, in use for more than 15 years 		
 Plug-in system allowing quick replacement for service or exchange 		
 Easy to maintain, needing few tools to service Low air consumption warning whistle with loud, even sound 		
 Reserve air valve as alternative warning system 		
 SCBA Fiber body composite cylinder with full face mask hanging back pack valve pressure hose and regulator 		
	TOTAL Rs.	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



 $\textbf{Email:}\ \underline{pmc1122kpk@gmail.com}, \underline{www.rescuekp.gov.pk}$

Specifications Lot-05

Subject: Water Rescue Stretcher

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1.	 Supply/ commissioning/testing of the Water Rescue Stretcher of the following specifications: - API Water Rescue Stretcher Width: 30-35 Inch Length: 80-90 Inch Weight: 16-18 Kg With Air Pump & 6-8 Carrying Straps To use for rescue unconscious peoples during emergency in river, drain & canal 	NO	15		
			TC	TAL Rs	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-06

Subject: Emergency Ambulatory Items

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1.	Supply of Emergency Ambulatory Items				
	Glucometer Machine	<u>NO</u>	100		
	Stethoscope		100	_	
	BP set Mercury		100	_	
	BP set Digital		100	_	
	Digital Thermometer		100	_	
	Nebulizer Machine (Portable)		100	_	
	Puls Oxymeter		100	_	
	Dead Body Sheet (with Rescue 1122 Logo)		1500	-	
	D/Syringe 5cc		35000	_	
	Hypertonic 25%		35000	-	
	Medical Gloves		3500	-	
	Surgical Tap		5000	-	
	RayBand Guazz		3000	-	
	IV Canola 22g,		3000	-	
	Surgical Silk 2/0		5000	_	
	IV canolla 20g		3000	_	
	Cotton roll 4"		4000	_	
	Cotton Roll 6"		15000	<u> </u>	
	Crep Bandage 4"		15000	_	
	Crep Bandage 3"		15000	-	
	Crep Bandage 6"		10000		
	Cotton roll 3"		20000	_	
	Sprit small		2000		
	Glucometer Needle		3000		
	Triangular Bandage		6000	-	
	Cotton Wool 100g		4000	<u> </u>	
	Face Mask		2000	<u> </u> -	
	Thermometer		2000	<u> </u> -	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



	TC	TAL	Rs.	
	200			
Extra Batteries for AED	250			
Defibrillator Graph Strips Pack	250			
Glucometer Strips 100 Strip/Pack	100			
ECG Gell (5L) can	500			
ECG Machine Electrodes (50) piece Pack	3000			
IV canolla 24g	1200			



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-07

Subject: Personal Protective Equipment's

Sr.	DESCRIPTION	Unit	Qty	Rate	Amount
1.	 Supply/ commissioning/testing of Fire Safety Helmet of the following specifications: - The product complies with GA44-2004 《Fire helmet requirements> standard, be used for head protection under emergency rescue. Have anti-sharp, anti-corrosive, anti-thermal radiation, reflection and insulation properties. The material of the shell: polyarmide fiber. Mask Imported high strength material (High heat resistance), transparent light yellow. Helmet interior could be adjustable, suitable for all kinds of people. Protective shawl: aluminum foil (heat resistance) Weight:1.3kgs. Yellow, red and customized color. Size: 73,59,48. 	NO	200		
2.	 Supply/ commissioning/testing of the Fire Gloves of the following specifications: - Be made of Aramid retardant materials, used for hand protection. Anti-slip, thermal resistant and flame □ retardant properties. Five finger design with good dexterity & power holding. Good feeling and super water-proof ability. Size: S-XL. 	NO	200		
3.	Supply/ commissioning/testing of the Flash Hood of the following specifications: - • Weight:115g-125g. • GA 869-2010 Standard. • Nomex material. • Formaldehyde content less than 75MG/KG. • white color.	NO	200		
4.	Safety Shoes • Upper split leather, Steel Toe, PU Sole Anti slip.	NO	1100		



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



5.	•	 Reflector. Fluorescent color, Mesh Fabric, with Reflector of front and back with Rescue Logos 							1500	
6.	 Rain Coat Rain Coat should be water proof, PVC Material, 1 pcs coat with Reflector 						NO	600		
7.	Safety	Jack	cets					NO	600	
		1	Co	mposition	Cotton I	Polyester				
		2	_	pe of eave	Poplin 1	/1				
		3	Co	nstruction	21x21/1	100x50				
		4	Fir	nishing	Soil rele	ease				
		5	Th	read	Core Sp	un tex.60				
		6	Pa	ttern	As per a	pproved				
8.	Uniform Cloth for Shirt & Trouser for 1500 Complete Uniform.					NO	1500			
	Items Shirt			Shirt		Trouser				
	Blend			Cotton: 65°		Cotton: 65%	% +-			
	Comp	osit	ion	Polyester: 5%	35 % +-	5% Polyester: 3 +- 5%	85 %			
	Weav	е Ту	ре	Ripstop 2/	1	Ripstop 2/	1			
	GSM			215 +- 5 %		215 +- 5 %				
	Count Yarn	of		18 x 18+- 2		18 x 18+- 2				
	Densi	ty P	er I	nch						
			_	02 +- 2 (End 3 +- 2 (Picks	-	102 +- 2 (Fig. 53 +- 2 (Pic.)	_			
	Dime:			Change (%)						
	Warp			X		1% Max				
	Weft 1% Max		1% Max							
	Natur Dying			Disperse/V	AT	Disperse/	VAT			
	Color			Mehendi Gr	een					
	Mono	grai		Rescue-1122 Khyber						
				Pakhtunkhv	va					



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



9.	.Beret	Сар					
	S#	Description	Specificati	on	NO	2000	
	1	Color	Blact Color approved	_			
	2	Wool	100% +- 5%	%			
	3	Quality of Wool	Good Qua	lity			
	4	Eyelet	2 Eyelet on	one side			
	5 Weight Grams as per size						
		6 3/4	80 Gram M	linimum			
		7	85 Gram M	linimum			
	7 1/4 90 Gra		90 Gram M	linimum			
	7 ½ 95 Gra			linimum			
		7 3/4	100 Gram	Minimum			
	6	Front Monogram Rescu		onogram			
	L						
10	Belt	5			NO	1500	
	S #	Description	Specification	-1 C -1			
	1	Material	Synthetic Blac				
	2	Width	3-3.5 cm depe	_			
	2	Duelrol	loops spacing				
	3	Buckel	Buckel made of embossed Res	-			
			monogram.	cuc			
11	T-Shi	rt	1		NO	1500	
	S#	Description	Sp	ecification			
	1	Color	_	own as per			
				proved			
			_	mple			
	2	Composition		otton 50%,			
				olyester 50%			
	3	Nature of Dye		sperse eactive			
	4	Monogram		s per			
	4	Monograni		proved			
				attern			
L			pa	111111111111111111111111111111111111111		1	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



weat	er		NO	600	
S#	Description	Specification			
1	Туре	Pullover ribbed			
		pattern V shaped full			
		sleeve having two			
		monograms			
2	Composition	Acrylic 75%,			
		polyester 20%,			
		nylon5%			
3	Color	Brown			
4	Colorfastness	Min grade 4			
5	Pockets	Two front pockets			
		with flaps			
6	Cloth	Drill cloth to be used			
		for elbow			
		TOTAL Rs.			·



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-08

Subject: Fire Extinguisher Ball

Sr.	DESCRIPT	DESCRIPTION			RATE	AMOUNT
6.	Supply of Fire Ball Medium Ammonium Phosphate)	: Dry Powder (Mono	<u>NO</u>	500		
	Coverage Area :	: 3-7 m2				
	Weight	: 1.2-1.4 kg				
	Diameter	: 150-160 mm				
	Activation Time	: 3 – 10 seconds				
	Warning Audio	: 100-120 dB				
	Possibility of failure failure is zero	: Possibility of				
	Life Span	: 60 Months				
	Size	: 6-7 inches' round				
	1		1	ТО	TAL Rs	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-09

Subject: Delivery Hose 2.5" (100 FT)

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT				
	 Supply of Fire Delivery Hose with the following specifications: - Dia 2.5" 100 Feet length roll poly propylene sheet red/white color with brass coupling Working pressure: 15-20 bar 	NO	300						
	TOTAL AMOUNT								



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-10

Subject: Chain Saw

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1.	Supply/ commissioning/testing of the Heavy Chain Saw of the following specifications: - PETROL ENGINE Displacement - 95-100 CM³ (Minimum) Power output 5-7 Kw Maximum weight 13.0 kg Sound Pressure Level 100-105 db(A) 5. Sound Power level 110-115 db(A) SAW ATTACHMENT Saw cutting depth 140-150 mm	NO	60	KATE	AMOUNT
	 Total length 80-90 mm Extra Cutting chains to be provide 06 Number 		TO	OTAL Rs	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-11

Subject: Dewatering Pump (Portable)

Sr.	DESCRIPTIO	N		UNIT	QTY	RATE	AMOUNT
1.	Supply of Dewatering	-	(Portable)	NO	60		
	(Imported) with the following	specifica	tions: -				
	Bore x Stroke (MM)	70	x55.	-			
	• Displacement (CM ³⁾	21	2.				
	Max. Output power	7.0)				
	(HP) • Starting System	Recoi	l/Electric				
	 Fuel tank Capacity (L) 	3.6	Ó				
	Continuous Operating time (H)	4					
	 Oil Capacity (L) 	0.6	6				
	 Dia. Of inlet/outlet 	3"	•				
	• Max. Lift (M)	26					
	• Suction (M)	8					
	• Max. Flux (m³/H	60					
	• N. W. (KG)	26					
	• G.W. (KG)	27					
	Carton size (CM)		x45x47				
	• 20GP/40HQ	20	8/520				



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-12

Subject: Hydraulic cutter with pump

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT				
2.	Supply/ commissioning/testing of the Hydraulic Cutter with Pump of the following specifications: - • Combi Tool • Cutting Force: 375-380 KN • Spreding Force: 205-215 KN • Pulling Force: 45-55 KN • Weight: 13.5-14.5 Kg • Pump • Working Pressure: 715-725 Bar • Engine Type: 4 Stroke • Weight: 14-15 Kg		03						
	TOTAL Rs.								



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-13

Subject: SCUBA Diving Kit.

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
6.	Supply/ commissioning/testing of the SCUBA of the following specifications: - • Half Face Mask • Gloves • Fins • Pressure Gauges • Regulator • Pressure Hoses • Air Tank 12 Ltr (Not Less than 12 Ltr) • Head Valve for Air Tank • Wet Suit • Compass • Dagger • Hard Case for Kit • Weight Belt • BCD Back Pack • Complete Set	ne <u>NO</u>	05		
			T	TAL Rs	; <u> </u>



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-14

Subject: Supply of Testing Commission of Air Flow system for Respiratory
Protection mainly used to prevent the inhalation of harmful gases,
dust etc. Follow are the specification/ Electric Rescue system with
Hose.

Sr.		DESCRIPT	ΓΙΟΝ		UNIT	QTY	RATE	AMOUNT
1.	1. Log Tube breathing apparatus composed of full facemask, belt long tube & fan. The equipment is respirational that should continuously supply fresh air through blower and a long tube respire for single use.					02		
	Working Power	220V	Operating voltage	12V DC				
	Fan Air Volume	19*0:/m m	Working Current	6.0A				
	Mask Air Volume	30L/mm	Rated Current	72W				
	Noise intensity	76db(A)	Executive Standard					
		1				TO	TAL Rs.	



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-15

Subject: Tripod With Pulley For Lifting Weight

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT		
	Supply/ commissioning/testing of the Tripod with Pulley for Lifting Weight of the following specifications: -		02				
	 Pulley for Lifting Weight 115-125 ft. Cable Max Weight 245-250 Kg 						
TOTAL Rs.							



EMERGENCY RESCUE SERVICE (RESCUE-1122) KHYBER PAKHTUNKHWA



Email: pmc1122kpk@gmail.com, www.rescuekp.gov.pk

Specifications Lot-16

Subject: Rescue Jumping Air Cushion (5x6.5x2.5)

Sr.	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1.	 Rescue jumping coushin a Life-saving mattress is a kind of air cushion to save high jump personnel, it is the safety equipment to protect fire rescue workers and air working stuffs. PVC Tarpaulin 0.45-0.55mm Height 2-3 meter Length 6-7 meter Width 4-6 meter Blower Size 50x40x50cm (not less than this size) Power 1.5 hp Repair kit, carry bag Warranty one year 	,	10		
	Total Amount				